


W Series



Type	Dimensions (mm)					Chamfer (r/min) Load(KN)	
	Д	Д	Б	A1	A2		
W0	4	14.84	6.35	5.94	9.12	0.3	1
W0X	4	14.84	6.35	5.94	9.12	0.3	1
W1	4.763	19.56	7.87	7.9.	11.86	0.3	2.2
W1X	4.763	19.56	7.87	7.93	11.86	0.3	2.2
W2	9.525	30.73	11.1	12.7	18.24	0.3	4.9
W2X	9.525	30.73	11.1	12.7	18.24	0.3	4.9
W3	12	45.72	15.88	19.05	26.98	0.6	9.4
W3X	12	45.72	15.88	19.05	26.98	0.6	9.4
W4	15	59.94	19.05	25.4	34.93	1	14.8
W4X	15	59.94	19.05	25.4	34.93	1	14.8
W4XL	22	75.39	25.4	31.75	44.45	1.1	20.6
W4XXL	22	75.39	25.4	31.75	44.45	1.1	20.6
W1SSX	4.763	19.56	7.87	7.93	11.86	0.3	2.2
W2SSX	9.525	30.73	11.1	12.7	18.24	0.3	4.9
W3SSX	12	45.72	15.88	19.05	26.98	0.6	9.4
W4SSX	15	59.94	19.05	25.4	34.93	1	14.8