



Designation	Principal Dimensions(mm)				Basic Load Ratings(KN)		Limited Speed(rpm)		Масса (kg)
	Д	Д	Б	рупий мин	Dynamic(Cr)	Static(Cor)	Смазка	Масло	
23022	110	170	45	2	282	455	1800	2800	3.71
23022K	110	170	45	2	282	455	1800	2800	3.58
23022KW33C3	110	170	45	2	282	455	1800	2800	3.58
23022W33C3	110	170	45	2	282	455	1800	2800	3.71
23024	120	180	46	2	296	495	1700	2600	4.05
23024K	120	180	46	2	296	495	1700	2600	3.9
23024KW33C3	120	180	46	2	296	495	1700	2600	3.9
23024W33C3	120	180	46	2	296	495	1700	2600	4.05
23026	130	200	52	2	375	620	1500	2300	5.9
23026K	130	200	52	2	375	620	1500	2300	5.69
23026KW33C3	130	200	52	2	375	620	1500	2300	5.69
23026W33C3	130	200	52	2	375	620	1500	2300	5.9
23028	140	210	53	2	405	690	1400	2200	6.35
23028K	140	210	53	2	405	690	1400	2200	6.12
23028KW33C3	140	210	53	2	405	690	1400	2200	6.12
23028W33C3	140	210	53	2	405	690	1400	2200	6.35
23030	150	225	56	2.1	445	775	1300	2000	7.73
23030K	150	225	56	2.1	445	775	1300	2000	7.45
23030KW33C3	150	225	56	2.1	445	775	1300	2000	7.45
23030W33C3	150	225	56	2.1	445	775	1300	2000	7.73
23032	160	240	60	2.1	505	885	1200	1900	9.42

23000 Series

23032K	160	240	60	2.1	505	885	1200	1900	9.09
23032KW33C3	160	240	60	2.1	505	885	1200	1900	9.09
23032W33C3	160	240	60	2.1	505	885	1200	1900	9.42
23034	170	260	67	2.1	630	1080	1100	1800	12.7
23034K	170	260	67	2.1	630	1080	1100	1800	12.3
23034KW33C3	170	260	67	2.1	630	1080	1100	1800	12.3
23034W33C3	170	260	67	2.1	630	1080	1100	1800	12.7
23036	180	280	74	2.1	740	1290	1100	1700	16.7
23036K	180	280	74	2.1	740	1290	1100	1700	16.1