



| Designation | Principal Dimensions(mm) |     |    | Basic Load Ratings(KN) |             | Limited Speed(rpm) |       | Масса (kg) |
|-------------|--------------------------|-----|----|------------------------|-------------|--------------------|-------|------------|
|             | Fw                       | Д   | Б  | Dynamic(Cr)            | Static(Cor) | Смазка             | Масло |            |
| RNU208E     | 50                       | 80  | 18 | 51.5                   | 53          | 7000               | 9000  | 0.25       |
| RNU209E     | 55                       | 85  | 19 | 58.5                   | 63.8        | 6300               | 8000  | 0.41       |
| RNU210E     | 60.4                     | 90  | 20 | 61.2                   | 68.2        | 6000               | 7500  | 0.43       |
| RNU212E     | 73                       | 110 | 22 | 89.8                   | 102         | 5000               | 6300  | 0.78       |
| RNU214E     | 84.5                     | 125 | 24 | 112                    | 135         | 4300               | 5300  | 0.89       |
| RNU218E     | 107                      | 160 | 30 | 172                    | 215         | 3400               | 4300  | 2.07       |
| RNU305E     | 35                       | 62  | 17 | 38.5                   | 35.8        | 9000               | 12000 | 0.2        |
| RNU306E     | 42                       | 72  | 19 | 49.2                   | 48.2        | 8000               | 10000 | 0.32       |
| RNU307E     | 46.2                     | 80  | 21 | 62                     | 63.2        | 7000               | 9000  | 0.4        |
| RNU308E     | 53.5                     | 90  | 23 | 76.8                   | 77.8        | 6300               | 8000  | 0.48       |
| RNU309E     | 58.5                     | 100 | 25 | 93                     | 98          | 5600               | 7000  | 0.79       |
| RNU310E     | 65                       | 110 | 27 | 105                    | 112         | 5300               | 6700  | 1.01       |
| RNU311E     | 70.5                     | 120 | 29 | 128                    | 138         | 4800               | 6000  | 1.5        |