

S6900 Series

Bearing NO.	Shape Dimension(mm)						Basic Load Rating(N)		Macca		
	d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic(Cr)	Static(Cor)	(kg)
S6900	10	0.3937	22	0.8661	6	0.2362	0.3	0.0118	2690	1270	0.0100
S6901	12	0.4724	24	0.9449	6	0.2362	0.3	0.0118	2890	1460	0.0120
S6902	15	0.5906	28	1.1024	7	0.2756	0.3	0.0118	4320	2250	0.0180
S6903	17	0.6693	30	1.1811	7	0.2756	0.3	0.0118	4590	2550	0.0190
S6904	20	0.7874	37	1.4567	9	0.3543	0.3	0.0118	6370	3680	0.0380
S6905	25	0.9843	42	1.6535	9	0.3543	0.3	0.0118	6660	4180	0.0440
S6906	30	1.1811	47	1.8504	9	0.3543	0.3	0.0118	7240	5010	0.0500
S6907	35	1.3780	55	2.1654	10	0.3937	0.6	0.0236	10390	7160	0.7500
S6908	40	1.5748	62	2.4409	12	0.4724	0.6	0.0236	13020	9200	0.1180
S6909	45	1.7717	68	2.6772	12	0.4724	0.6	0.0236	13490	10130	0.1280
S6910	50	1.9685	72	2.8346	12	0.4724	0.6	0.0236	13900	10990	0.1330